

602946-60 MOBIL SHC 629  
MATERIAL SAFETY DATA BULLETIN

-----  
---

-----  
---  
1. PRODUCT AND COMPANY IDENTIFICATION  
-----

-----  
---  
PRODUCT NAME: SHC 629  
MANUFACTURER CODE: 602946  
CMCS CODE: 970114  
SUPPLIER: MOBIL OIL AUSTRALIA PTY LTD A.B.N. 88 004 052 984  
12 RIVERSIDE QUAY  
SOUTHBANK, VICTORIA 3006  
AUSTRALIA

After hours: National Emergency Communication System 1-800-023-005  
Product Information contact: 1-800-033-863

Supplier General Contact: 1-800-631-296

Worksafe Classification: Not classified as hazardous according to  
criteria of Worksafe Australia.

-----  
---  
2. COMPOSITION/INFORMATION ON INGREDIENTS  
-----

---  
GENERIC COMPOSITION: SYN. HYDROCARBONS AND ADDITIVES

---  
GLOBALLY REPORTABLE MSDS INGREDIENTS:

None.

-----  
---  
3. HAZARDS IDENTIFICATION  
-----

---  
This product is not considered hazardous according to regulatory  
guidelines (See Section 1).

POTENTIAL HEALTH EFFECTS: Under normal conditions of intended use,  
this product does not pose a risk to health. Excessive exposure  
may result in eye, skin or respiratory irritation.

For further health effects/toxicological data, see Section 11.

-----  
---  
4. FIRST AID MEASURES

-----  
---  
EYE CONTACT: Flush thoroughly with water. If irritation persists, call a doctor.  
SKIN CONTACT: Wash contact areas with water. Remove and clean oil soaked clothing daily and wash affected area. (See Section 16 - Injection Injury)  
INHALATION: Not expected to be a problem. However, if respiratory irritation, dizziness, nausea, or unconsciousness occurs due to excessive vapour or mist exposure, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or mouth-to-mouth resuscitation.  
INGESTION: Not expected to be a problem. Seek medical attention if discomfort occurs. Do not induce vomiting.  
NOTE TO PHYSICIANS: Treat symptoms with reference to specific health effects identified above.

-----  
---  
5. FIRE-FIGHTING MEASURES  
-----  
---

EXTINGUISHING MEDIA: Foam, dry chemical, CO2 and water fog.  
SPECIAL FIRE FIGHTING PROCEDURES: Water or foam may cause frothing. Use water to cool fire-exposed containers. Water spray may be used to flush spills away from exposures. Prevent runoff from fire control or dilution from entering waterways, sewers or drinking water supply.  
SPECIAL PROTECTIVE EQUIPMENT: For fires in enclosed areas, firefighters must use self-contained breathing apparatus.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: None.  
COMBUSTION PRODUCTS: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.  
Flash Point C (F): 228(442) (IP 34 / ASTM D-93).  
Flammable Limits (approx.% vol.in air)- LEL 0.9%, UEL: 7.0%  
NFPA HAZARD ID: Health: 0 , Flammability: 1 , Reactivity: 0

-----  
---  
6. ACCIDENTAL RELEASE MEASURES  
-----  
---

NOTIFICATION PROCEDURES: Report spills as required to appropriate authorities. In case of accident or road spill, contact the Police and Fire Brigade and, if appropriate, the Area Water Authority.  
PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:  
LAND SPILL: Shut off source taking normal safety precautions. Take measures to minimize the effects on ground water. Recover by pumping or contain spilled material with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of adsorbed residues as directed in Section 13.  
WATER SPILL: Confine the spill immediately with booms. Warn other ships in the vicinity. Notify port and other relevant

authorities. Remove from the surface by skimming or with suitable absorbents. If permitted by regulatory authorities the use of suitable dispersants should be considered where recommended in local oil spill procedures.

ENVIRONMENTAL PRECAUTIONS: Prevent material from entering sewers, water sources or low lying areas; advise the relevant authorities if it has, or if it contaminates soil/vegetation.

PERSONAL PRECAUTIONS: See Section 8

---

7. HANDLING AND STORAGE

---

HANDLING: No special precautions are necessary beyond normal good hygiene practices. See Section 8 for additional personal protection advice when handling this product.

STORAGE: Keep containers closed when not in use. Do not store in open or unlabelled containers. Store away from strong oxidizing agents and combustible materials. Do not store near heat, sparks, flame or strong oxidants. See Section 15 for Regulatory information when storing this product.

SPECIAL PRECAUTIONS: Prevent small spills and leakages to avoid slip hazard.

EMPTY CONTAINER WARNING: Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

OCCUPATIONAL EXPOSURE LIMITS:

When mists/aerosols can occur, the following is recommended: 5 mg/m<sup>3</sup> as oil mist (NOHSC).

VENTILATION: If mists are generated, use adequate ventilation, local exhaust or enclosures to control below exposure limits.

RESPIRATORY PROTECTION: If mists are generated, and/or when ventilation is not adequate, wear approved respirator.

EYE PROTECTION: If eye contact is likely, safety glasses with side shields or chemical type goggles should be worn.

SKIN PROTECTION: When splashing or liquid contact can occur frequently, wear oil resistant gloves and/or other protective clothing. Good personal hygiene practices should always be followed.

-----  
---  
9. PHYSICAL AND CHEMICAL PROPERTIES  
-----

---  
Typical physical properties are given below. Consult Product Data Sheet for specific details.

PHYSICAL STATE: Liquid  
COLOUR: Orange  
ODOUR: Mild  
ODOUR THRESHOLD (ppm): NE  
pH: NA  
Boiling Point C (F): > 260(500)  
Melting Point C (F): NA  
Flash Point C(F): 228(442) (IP 34 / ASTM D-93)  
FLAMMABILITY (solids): NE  
AUTO FLAMMABILITY C(F): NA  
EXPLOSIVE PROPERTIES: NA  
OXIDIZING PROPERTIES: NA  
Vapour Pressure-mm Hg 20 C: < 0.1  
VAPOUR DENSITY: > 2.0  
EVAPORATION RATE: NE  
Relative Density, 15/4 C: 0.864  
Solubility in Water: Negligible  
PARTITION COEFFICIENT: > 3.5  
Viscosity at 40 C, cSt: 142.8  
Viscosity at 100 C, cSt: 18.3  
Pour Point C: -45(-49)  
FREEZING POINT C(F): NE  
DMSO EXTRACT, IP-346 (WT.%): <3, for mineral oil only  
NA=Not Applicable, NE=Not Established, D=Decomposes

For further technical information, contact your Mobil Marketing Representative.

-----  
---  
10. STABILITY AND REACTIVITY  
-----

---  
STABILITY (Thermal, Light, etc.): Stable.  
CONDITIONS TO AVOID: Extreme heat and high energy sources of ignition.  
INCOMPATIBILITY (Materials to Avoid): Strong oxidisers.  
HAZARDOUS DECOMPOSITION PRODUCTS: Product does not decompose at ambient temperatures.  
HAZARDOUS POLYMERISATION: Will not occur.

-----  
---  
11. TOXICOLOGICAL DATA  
-----

---ACUTE TOXICOLOGY---  
ORAL TOXICITY: Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the

components.

DERMAL TOXICITY: Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.

INHALATION TOXICITY: Practically non-toxic ---Based on testing of similar products and/or the components.

EYE IRRITATION: Practically non-irritating. (Draize score: greater than 6, but 15 or less). ---Based on testing of similar products and/or the components.

SKIN IRRITATION: Practically non-irritating. (Primary Irritation Index: greater than 0.5, but less than 3). ---Based on testing of similar products and/or the components.

OTHER ACUTE TOXICITY DATA: Although an acute inhalation study was not performed with this product, a variety of mineral and synthetic oils, such as those in this product, have been tested. These samples had virtually no effect other than a nonspecific inflammatory response in the lung to the aerosolized mineral oil. The presence of additives in other tested formulations (in approximately the same amounts as in the present formulation) did not alter the observed effects.

---SUBCHRONIC TOXICOLOGY (SUMMARY)---

No significant adverse effects were found in studies using repeated dermal applications of similar formulations to the skin of laboratory animals for 13 weeks at doses significantly higher than those expected during normal industrial exposure. The animals were evaluated extensively for effects of exposure (hematology, serum chemistry, urinalysis, organ weights, microscopic examination of tissues etc.).

---REPRODUCTIVE TOXICOLOGY (SUMMARY)---

No teratogenic effects would be expected from dermal exposure, based on laboratory developmental toxicity studies of major components in this formulation and/or materials of similar composition.

---CHRONIC TOXICOLOGY (SUMMARY)---

Repeated and/or prolonged exposure may cause irritation to the skin, eyes or respiratory tract. Overexposure to oil mist may result in oil droplet deposition and/or granuloma formation. For mineral base oils: Base oils in this product are severely solvent refined and/or severely hydrotreated. Chronic mouse skin painting studies of severely treated oils showed no evidence of carcinogenic effects. These results are confirmed on a continuing basis using various screening methods such as Modified Ames Test, IP-346, and/or other analytical methods. For synthetic base oils: The base oils in this product have been tested in the Ames assay and other tests of mutagenicity with negative results. These base oils are not expected to be carcinogenic with chronic dermal exposures.

---SENSITIZATION (SUMMARY)---

Not expected to be sensitizing based on tests of this product, components, or similar products.

-----  
---

12. ECOLOGICAL INFORMATION

-----  
---

ENVIRONMENTAL FATE AND EFFECTS:

In the absence of specific environmental data for this product, this assessment is based on information for representative products.

ECOTOXICITY: Available ectotoxicity data (LL50 >1000 mg/L) indicates that adverse effects to aquatic organisms are not expected from this product.

MOBILITY: When released into the environment, adsorption to sediment and soil will be the predominant behavior.

PERSISTENCE AND DEGRADABILITY: This product is expected to be inherently biodegradable.

BIOACCUMULATIVE POTENTIAL: Bioaccumulation is unlikely due to the very low water solubility of this product, therefore bioavailability to aquatic organisms is minimal.

-----  
---

13. DISPOSAL CONSIDERATIONS

-----  
---

WASTE DISPOSAL: Product is suitable for burning in an enclosed, controlled burner for fuel value. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate licensed waste disposal site. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

-----  
---

14. TRANSPORT INFORMATION

-----  
---

ACTDG: NOT REGULATED BY ACTDG.

IMO: NOT REGULATED BY IMO

IATA: NOT REGULATED BY IATA

STATIC ACCUMULATOR (50 picosiemens or less): YES

-----  
---

15. REGULATORY INFORMATION

-----  
---

Australian Classifications:

UN Number: NA  
HAZCHEM Code: Not applicable  
Dangerous Goods Class/Subsidiary Risk: Not applicable  
Packaging Group: NA  
AS 1940 Class: C2  
Poisons Schedule: Not applicable

EC Labeling: Product is not dangerous as defined by the European Union Dangerous Substances/Preparations Directives. EU labeling not required.

Governmental Inventory Status: All components comply with European EINECS/ELINCS and US TSCA.

THE FOLLOWING PRODUCT INGREDIENTS ARE CITED ON THE LISTS BELOW:

CHEMICAL NAME CAS NUMBER LIST CITATIONS  
\*\*\* NO REPORTABLE INGREDIENTS \*\*\*

--- REGULATORY LISTS SEARCHED ---

1=IARC 1 2=IARC 2A 3=IARC 2B 4=NTP CARC 5=NTP SUS  
6=ACGIH 7=ACGIH CARC 8=ACGIH SUS

CARC=CARCINOGEN; SUS=SUSPECTED CARCINOGEN; TERAT=TERATOGENIC

-----  
---  
16. OTHER INFORMATION  
-----  
---

USE: GEAR AND BEARING LUBRICANT

NOTE: EXXONMOBIL PRODUCTS ARE NOT FORMULATED TO CONTAIN PCBS.

Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. Information provided on this MSDS reflects intended use. This product should not be used for other applications. In any case, the following advice should be considered:

INJECTION INJURY WARNING: If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

INDUSTRIAL LABEL

Under normal conditions of use, this product should not pose a risk to health. However, users should avoid overexposure to liquids and mists

which may result in eye,skin or respiratory irritation. Always observe good hygiene measures. First Aid: Wash skin with soap and water. Flush eyes with water. If overcome by fumes or vapor,remove to fresh air. If ingested, do no induce vomiting. If symptoms persist seek medical assistance. Read and understand the MSDS before using this product.

This MSDS meets Worksafe Australia accepted format requirements.  
\*\*\*\*\*  
For Internal Use Only: MHC: 1\* 1\* 1\* 1\* 1\*, MPPEC: A, TRN:  
602946-60, ELIS: 400008, CMCS97: 970114  
Issue Date: 21AUG2001  
\*\*\*\*\*

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

Prepared by: Exxon Mobil Corporation  
EMBSI, Clinton, NJ USA  
For further information, contact:  
See Section 1 for Local Contact number